

BETTER SECURITY  
BETTER SOLUTION

CYBERTRON®

## CYB-B24PH-SL12

2.4MP HD Bullet Camera-20mtr

- 1/2.9" 2.4MP CMOS Image Sensor
- 25/30fps@2.4MP
- DWDR, Day/Night (ICR), 2D-DNR, AWB, AGC, BLC
- 3.6mm lens (6mm optional)
- Support low illumination
- IR Range of 20mtr



### Functions

#### IR LED

Numerous IR LEDs provide detailed images even in very low light conditions. These LEDs adjust the infrared intensity for distinct images in dark environments for up to 20mtrs.

CYBERTRON HD cameras offer compatibility across all the available technologies - CVBS, TVI, HDCVI, AHD making upgrading simple and hassle-free

BETTER SECURITY  
BETTER SOLUTION

CYBERTRON<sup>®</sup>



## CYB-B24PH-SL12

2.4MP HD Bullet Camera-20mtr

Feature	Specification
Image sensor	1/2.9" HD-CMOS
Resolution	PAL/NTSC: 1920x1080P
Frame rate	25/30fps@2.4mp
Minimum illumination	0.1 Lux (Color/Day) 0Lux (B/W)
Shutter type	1/50(1/60)s-1/100,000s
Camera pixel	2.4MP (1920x1080P)
White balance	Auto tracking white balance
OSD function	Optional
Lens furnished	3.6mm MP HD Lens
Lens type	HD Lens / IR cut filter
Gain control	Auto
3D-DNR	Auto
IR Led / IR distance	12-IR LED/ up to 20mtr
Video output	AHD-BNC
Power source	12VDC+10%
Current drawn	500mA (Max.)
Operating temperature	-10°C to +55°C

 [Sales@cybertroncctv.com](mailto:Sales@cybertroncctv.com)

 [Rma@cybertroncctv.com](mailto:Rma@cybertroncctv.com)

 [Info@cybertroncctv.com](mailto:Info@cybertroncctv.com)

 [Support@cybertroncctv.com](mailto:Support@cybertroncctv.com)